

PJS-F EXTRA



GENERAL FEATURES

- Strong heavy duty metal frame
- Impact resistant plastic injection covers
- Convenient storage for gun and lance
- Large capacity diesel tank (19 ltrs) with vertical type diesel level sensor
- Built in detergent tank (16 ltrs)
- High pressure detergent system with regulation
- Water suction from tank with floater
- Water softener device with pump and tank
- Easy to check water filter
- Large rubber wheels (Ø300mm)

TECHNICAL FEATURES

- Heavy duty 4 poles electric motor (1400 rpm) with external anti corrosion protection
- Exclusive coupling system between pump and motor for heavy duty use
- Professional pressure release unloader valve
- Self priming pumps (with **EASY-START** device, only for single phase version; motor guaranteed to start in all electrical conditions)
- Delayed **TOTAL STOP**
- General Shutdown (when machine not used for a while)

CONTROL PANEL

- **Low voltage controls**
- **Remote Control Switch**
- **Motor Protected with Thermal Relay**
- **Rotating Switch for hot/cold**
- **Temperature adjustment knob**
- **"Machine switched on" lamp**
- **"Timed Shutdown" lamp**
- **"Motor Thermal Overload" lamp**
- **"Leak detected" lamp. Protect motor from unexpected starting**
- **"Steam shutdown" lamp**
- **"Low fuel level" lamp**
- **"Burner malfunction" lamp**

BOILER FEATURES

- **Double coil vertical boiler**
- **S.Steel external boiler body**
- **High thermal efficiency**
- **Constant water temperature**
- **Burner controlled by flow switch**
- **Delayed burner start**
- **Flame control device system**
- **Safety valve**
- **Boiler thermal protector**

ACCESSORIES

- **Hose Reel**
- **Foam Lance**
- **Drain Nozzle**
- **Sandblasting Lance**
- **Complete Gun and Lance with Swivel**
- **Adjustable Lance**
- **Twin Lance**
- **Lance with Rotating Nozzle**

TECHNICAL DATA

Model	Max flow rate (LPH)	Max Pressure (BAR)	Voltage	Absorbed power (HP)	RPM	Weight (KG)	Dimensions (LXBXH) cm
PJS-F-EXTRA-10.110	600	110	230 V (1-50 HZ)	4	1400	144	132 X 82 X 96
PJS-F-EXTRA-15.160	900	160	400 V (3-50 HZ)	7.5		154	
PJS-F-EXTRA-15.200	900	200		10		154	
PJS-F-EXTRA-18.200	1080	200		10		160	
PJS-F-EXTRA-21.170	1260	170		10		160	
PJS-F-EXTRA-18.230	1080	230		12.5		165	
PJS-F-EXTRA-21.210	1260	210		15		165	



PressureJet Systems Pvt. Ltd.

62/13, Phase-1, G.I.D.C., Vatva, Ahmedabad-382 445. Gujarat, India.
 Phone: +91-079-25835598/25830762/25893868, Fax: +91-079-25897220.
 Email: sales@pressurejet.com URL: www.pressurejet.com