

# PJS-VENTO



## GENERAL FEATURES

- Three-pistons axial pump, flanged directly to the electric motor
- Bras manifold
- Convenient storage for gun and lance.
- Pressure gauge
- Built-in fuel and detergent tanks
- **EASY-START** device motor guaranteed to start in all electrical conditions
- Direct feed to water pump with low pressure detergent system
- **TOTAL STOP**

## CONTROL PANEL

- Amperometric Motor Protector
- On-off Switch
- Temperature adjustment knob

## BOILER FEATURES

- Double coil vertical boiler
- High thermal efficiency
- Delayed burner start
- Safety valve

## ACCESSORIES

- Foam Lance
- Drain Nozzle
- Sandblasting Lance
- Adjustable Lance
- Twin Lance
- Lance with Rotating Nozzle
- Ionic Anti-scale Device

### TECHNICAL DATA

Model	Max flow rate (LPH)	Max Pressure BAR)	Voltage	Absorbed power (HP)	RPM	Weight (KG)	Dimensions (LXBXH) cm
<b>PJS-V-9.150</b>	540	150	230 V (1-50 HZ)	4	2800	85	89X50 X 82
<b>PJS-V-10.135</b>	600	135					

## PressureJet Systems Pvt. Ltd.

62/13, Phase-1, G.I.D.C., Vatva, Ahmedabad-382 445. Gujarat, India.  
Phone: +91-079-25835598/25830762/25893868, Fax: +91-079-25897220.  
Email: [sales@pressurejet.com](mailto:sales@pressurejet.com) URL: [www.pressurejet.com](http://www.pressurejet.com)